




SPECIFICATIONS

Marketing Name	GeForce RTX™ 5090 32G SUPRIM SOC
Modèle	G5090-32SPS
Processeur graphique	NVIDIA® GeForce RTX™ 5090
Cœurs	21760 unités
Mémoire	32 Go GDDR7
Bus Mémoire	512-bit
Fréquence du GPU	Mode Gaming : - Performances extrêmes : 2580 MHz (MSI Center) - Boost : 2565 MHz
	Mode Silent : - Performances extrêmes : 2527 MHz (MSI Center) - Boost : 2512 MHz
Vitesse mémoire	28 Gb/s
Nombre d'écrans supportés	4
Technologie G-SYNC™	Oui
Résolution numérique maximum	7680 x 4320
Support du procédé HDCP	Oui
Bloc d'alimentation recommandé	1000 W
Connecteurs alimentation	1 x 16 broches
Sorties	3 x DisplayPort (2.1b) 1 x HDMI™ (caractéristiques du HDMI™ 2.1b : jusqu'à 4K 480 Hz ou 8K 120 Hz avec DSC, Gaming VRR, HDR)
Version OpenGL	4.6
Dimensions	359 x 150 x 76 mm
Poids	2840 g / 3695 g

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



HYPER FROZR THERMAL DESIGN

An apex evolution of advanced thermal design that delivers unparalleled cooling and quiet operation.



STORMFORCE FAN

Seven fan blades, claw texturing, and a circular arc are designed for optimal airflow with minimal noise.




Advanced Vapor Chamber

Built-in Vapor Chamber swiftly transfers heat from the GPU and VRAM to the core pipe for optimal dissipation.




Optimized Heat Distribution - Core Pipe

Square-shaped Core Pipes maximize heat dissipation with the Vapor Chamber for superior cooling.



Wave Curved 4.0

Precision-engineered wave edges with a high-low fin design enhance airflow and reduce turbulence.



Air Antegrade Fin 2.0

The fins feature a V-shaped cutout and a high-low design at the airflow passthrough to optimize flow efficiency.



Metal Backplate

A reinforcing metal backplate with airflow vents and thermal pads enhances cooling.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.