

Be Your Window To The World



Picture and logos

SELLING POINTS

- Courbure 1500R pour une expérience immersive que ce soit pour travailler ou se divertir
- Certification TÜV qui garantit la bonne protection de vos yeux
- Technologies antiscintillement et de réduction de la lumière bleue
- Logiciel MSI Display Kit pour paramétrer au mieux l'affichage
- Taux de rafraîchissement de 100 Hz pour une meilleure expérience
- Connecteurs DisplayPort et HDMI™
- Compatible à la norme de fixation VESA
- Haut-parleurs intégrés



1. 1x DC Jack
2. 1x HDMI™ (1.4)
3. 1x D-Sub (VGA)
4. 1x Line-in
5. 1x Headphone-out
6. 1x Kensington Lock
7. 1x 5-Way Navigator + OSD Button

SPECIFICATION

Modèle	Entity MKT Name	PRO MP341CQ
	Part No	9S6-3PB2CT-032
	Color	ID1/Black-Black
Affichage	Screen Size	34" (86.36 cm)
	Active Display Area (mm)	797.22(H)x333.72(V)
	Curvature	Curve 1500R
	Panel Type	VA
	Resolution	3440x1440 (UWQHD)
	Pixel pitch (mm)	0.23175(H)x0.23175(V)
	Aspect Ratio	21:9
	Dynamic Refresh Rate technology	FreeSync
	Dynamic Refresh Rate Activated Range	48~100Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	3000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	58.56~148.1 KHz(H) / 48~100 Hz(V)
	Refresh Rate	100HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	101.36% / 86%
	NTSC (CIE1931 area percentage/overlap)	86.07% / 80.08%
	sRGB (CIE1976 area percentage/overlap)	116.25% / 98.55%
	sRGB (CIE1931 area percentage/overlap)	121.52% / 99.62%
	Adobe RGB (CIE1976 area percentage/overlap)	99.62% / 89.57%
	Adobe RGB (CIE1931 area percentage/overlap)	90.06% / 83.53%
	DCI-P3 (CIE1976 area percentage/overlap)	92.58% / 91.96%
	DCI-P3 (CIE1931 area percentage/overlap)	89.58% / 89.17%
	Rec.709 (CIE1976 area percentage/overlap)	116.25% / 98.55%
	Rec.709 (CIE1931 area percentage/overlap)	121.52% / 99.62%
	Rec.2020 (CIE1976 area percentage/overlap)	67.46% / 67.46%
	Rec.2020 (CIE1931 area percentage/overlap)	64.27% / 64.27%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
	Color bit	10 bits (8 bits + FRC)
Ports E/S	Headphone-out	1
	Lock type	Kensington Lock
	Speaker	2
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.2
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	2.2
	DisplayPort HDCP version	2.2
Garantie	Warranty	24M
Alimentation	Power Type	Power Cable
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	33
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	G
	Power Cord Type	C13



PRO MP341CQ

PRO MP341CQ

Accessoires	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-3.5° ~ 21.5°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	809.3 x 237.0 x 469.5
	Product Dimension without Stand (WxDxH) (mm)	809.3 x 106.8 x 365.8
	Stand Dimension (WxDxH) (mm)	240.0 x 237.0 x 176.6
	Weight (Net kg)	7.7
	Weight Without Stand (kg)	6.5
Dimensions et poids (carton)	Inside Carton Dimension (WxDxH) (cm)	98 x 18.7 x 49
	Outer Carton Dimension (WxDxH) (cm)	99.8 x 20.2 x 51.5
	Weight (Gross kg)	10.3
Code-barre	EAN	4719072960964