

Product data sheet

Specifications



Rack PDU, Basic, Zero U, 10A,230V, (15)C13



AP9568

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	120 V 200 V 208 V 230 V 240 V
PDU Type	Basic
Main Output Voltage	208 V 230 V
Input Connection Type	IEC 60320 C14
Number of rack unit	0U
Cable length	6.5 ft (1.98 m)
Number of cables	1
Provided Equipment	Installation guide Rack Mounting brackets Toolless Mounting Kit

Physical

Color	Black
Height	24.02 in (61 cm)
Width	1.73 in (4.4 cm)
Depth	1.73 in (4.4 cm)
Product Weight	4.41 lb(US) (2 kg)
Mounting Location	Side
Mounting preference	No preference
Mounting Mode	Rack-mounted
Mounting position	Vertical

Input

Acceptable Input Voltage	100...240 V
Input current limits	10 A
Load Capacity	2300 VA

Input Frequency	50/60 Hz
Output	
Number of power socket outlets	15 IEC 60320 C13
Conformance	
Product Certifications	cUL Listed CE GOST Queensland Australia UL Listed VDE
Environmental	
Ambient Air Temperature for Operation	32...113 °F (0...45 °C)
Relative Humidity	0...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0.00...15240.00 m)
Ordering and shipping details	
GTIN	731304207054
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.51 in (64.8 cm)
Package 1 Width	7.01 in (17.8 cm)
Package 1 Length	5.98 in (15.2 cm)
Package 1 Weight	6.01 lb(US) (2.724 kg)
Offer Sustainability	
Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available
Contractual warranty	
Warranty	2 years repair or replace

Recommended replacement(s)