




## SPECIFICATIONS

|                                        |                                                                                                                                                                   |
|----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product Name</b>                    | MPG VELOX 300R AIRFLOW PZ / WHITE                                                                                                                                 |
| <b>Case Form Factor</b>                | Mid-Tower                                                                                                                                                         |
| <b>Motherboard Form Factor Support</b> | Regular:<br>EATX (up to 305 x 278mm), ATX, Micro-ATX, Mini-ITX<br>Back-connect:<br>ATX                                                                            |
| <b>I/O Ports</b>                       | 1 x USB 20Gbs (Type-C)<br>2 x USB 5Gbs (Type-A)<br>1 x Audio-Out / Mic-in<br>1 x LED Button<br>1 x Power Button                                                   |
| <b>Drive Mount Support</b>             | 4 x 2.5"<br>1 x 3.5"<br>1 x 2.5"/3.5" combo                                                                                                                       |
| <b>Expansion Slots</b>                 | 7                                                                                                                                                                 |
| <b>Maximum GPU Length</b>              | 400 mm / 15.75 inches                                                                                                                                             |
| <b>Maximum CPU Cooler Height</b>       | 165 mm / 6.50 inches                                                                                                                                              |
| <b>Power Supply Support</b>            | ATX                                                                                                                                                               |
| <b>Maximum PSU Length</b>              | 200 mm / 7.87 inches                                                                                                                                              |
| <b>Fan Size Support</b>                | Front: 3 x 120 mm / 3 x 140 mm / 2 x 160 mm<br>Rear: 1 x 120 mm<br>Top: 3 x 120 mm / 3 x 140 mm<br>Side: 3 x 120 mm<br>PSU Shroud: 2x120 mm<br>Bottom: 1 x 120 mm |
| <b>Pre-installed Fan Size</b>          | Front: 2 x 160 mm<br>Rear: 1 x 120 mm                                                                                                                             |
| <b>Pre-installed Fan Type</b>          | Front: 2 x ARGB Fan (Dual Layer Blades Fan, Rifle Bearing)<br>Rear: 1 x Non-ARGB Fan ( Dual Layer Blades Fan, Rifle Bearing)                                      |
| <b>Radiator Size Support</b>           | Front: 120 / 140 / 240 / 280 / 360 mm<br>Rear: 120 mm<br>Top: 120 / 140/ 240 / 280 / 360 mm<br>Side: 120 / 240 / 360 mm<br>Bottom: N/A                            |
| <b>Dimensions (DxWxH)</b>              | 485 x 235 x 518 mm / 19.09 x 9.25 x 20.39 inches                                                                                                                  |

## FEATURES



### Support Back Back-Connect ATX Motherboard

Compatible with ATX PROJECT ZERO motherboards, allowing easy installation and streamlined cable management by routing cables through the rear.



### Airflow Optimized

Features a diamond diamond-cut ventilation front panel with two 16cm fans in the front and a 12cm fan at the rear, creating an optimized airflow channel.



### Dual Layer Blades Fan

The dual-layer fan consists of outer and inner ring blades that rotate simultaneously, creating two airflow speeds for concentrated airflow and enhanced heat dissipation.



### Versatile Cooling Support

Wide range of compatibility available for equipped up to 13 pieces of Fan, 3 pieces of 360mm Radiator, 1 piece of Pump Reservoir or one set of water cooling distro plate.



### Fan Speed Control

Three fan speed levels provides customizable settings to suit various scenarios.



### EZ PSU Cover


Quick snap-andand-lock PSU cover enables easy assembly and streamlined cable management, optimizing the PC build process.



### EZ Bracket

The adjustable EZ bracket supports fan sizes of 160mm x 2, 140mm x 3, and 120mm x 3, as well as a water cooling distro plate, allowing for flexible installation and optimized airflow.

## CONNECTIONS



1. 1 x USB 20Gbs (Type-C)
2. 2 x USB 5Gbs (Type-A)
3. Mic In/ Audio Out
4. LED Button
5. Power Button