


SPECIFICATIONS

Modèle	GeForce RTX™ 4070 SUPER 12G VENTUS 2X OC
Processeur graphique	NVIDIA® GeForce RTX™ 4070 SUPER
Cœurs	7168 unités
Mémoire	12 Go GDDR6X
Bus Mémoire	192-bit
Fréquence du GPU	Extreme Performance : 2520 MHz (MSI Center) Boost : 2505 MHz
Vitesse mémoire	21 Gb/s
Nombre d'écrans supportés	4
Technologie G-SYNC™	Oui
Résolution numérique maximum	7680 x 4320
Support du procédé HDCP	Oui
Bloc d'alimentation recommandé	650 watts
Connecteurs alimentation	1 x 16 broches
Sorties	3 x DisplayPort (v1.4a) 1 x HDMI™ (Support 4K @ 120 Hz HDR, 8K @ 60 Hz HDR et de la fréquence de rafraîchissement variable telle que spécifiée par la norme HDMI™ 2.1a)
Version OpenGL	4.6
Dimensions	242 x 125 x 43 mm
Poids	680 g / 998 g

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



Dual Fan

Two fans and a huge heatsink ensure a cool and quiet experience for you.



TORX FAN 4.0

A masterpiece of teamwork, fan blades work in pairs to create unprecedented levels of focused air pressure.



Copper Baseplate

A solid nickel-plated copper baseplate transfers heat from the GPU to all heat pipes for better cooling.




Core Pipe

Precision-machined heat pipes ensure max contact to the GPU and spread heat along the full length of the heatsink.



Reinforcing Backplate

The reinforcing backplate features a flow-through design that provides additional ventilation.



Zero Frozr

The fans completely stop when temperatures are relatively low, eliminating all noise.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Afterburner

Take full control with the most recognized and widely used graphics card overclocking software in the world.