

PATH TO THE FUTURE

The Most Efficient & Professional Monitor The MSI PRO MP241X Full HD LED monitor, with HDMI & VGA interfaces, is optimized for the finest image and color quality with a IPS grade panel. It is designed for your programming, coding & website design workspace. It not only makes every line & detail clear for your projects but also let you enjoy the smoothest streaming & on-line video experience.



Selling Points

- Un écran 23,8" parfait pour la programmation, le codage et le design
- Certification TÜV qui assure une excellente protection de yeux
- Technologie antiscintillement et de réduction de la lumière bleue
- Taux de rafraîchissement de 75 Hz pour une meilleure expérience
- Résolution Full HD (1920 x 1080) pour un streaming et des réunions en ligne parfaite
- Logiciel MSI Display Kit pour paramétrer au mieux l'affichage
- Connecteurs VGA et HDMI
- Compatible à la norme de fixation VESA



Picture and logos

System I/O-Ports



1. 1x HDMI (1.4)
2. 1x D-Sub(VGA)
3. 1x DC Jack
4. 1x Kensington Lock

Specification

Display	Screen Size	23.8" (60cm)
	Active Display Area (mm)	534.04(H)x307.76(V)
	Curvature	Flat
	Panel Type	VA
	Resolution	1920x1080 (FHD)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	HDR (High dynamic range)	N/A
	SDR Brightness (nits)	250
	Contrast Ratio	3000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	24~85 KHz(H) / 48~75 Hz(V)
	Refresh Rate	75Hz
	Response Time (GTG)	4ms
	Response Time (Tr + Tf)	19ms
	View Angles	178°(H)/178°(V)
	Surface Treatment	Anti-glare
	NTSC (CIE1976 area percentage/overlap)	92%/76%
	NTSC (CIE1931 area percentage/overlap)	92%/72%
	sRGB (CIE1976 area percentage/overlap)	105%/92%
	sRGB (CIE1931 area percentage/overlap)	102%/92%
	Adobe RGB (CIE1976 area percentage/overlap)	90%/80%
	Adobe RGB (CIE1931 area percentage/overlap)	76%/71%
	DCI-P3 (CIE1976 area percentage/overlap)	84%/81%
	DCI-P3 (CIE1931 area percentage/overlap)	75%/75%
	Rec.709 (CIE1976 area percentage/overlap)	105%/92%
	Rec.709 (CIE1931 area percentage/overlap)	102%/92%
	Rec.2020 (CIE1976 area percentage/overlap)	62%/61%
	Rec.2020 (CIE1931 area percentage/overlap)	54%/54%
	Display Colors	16.7M
	Color bit	8 bits
	Note_HDMI™	1920 x 1080 (Up to 75Hz)
	Note_DVI	N/A
I/O Ports	Line-in	N/A
	HDMI™ version	1.4b
	HDMI™ HDCP version	1.4
	Lock type	Kensington Lock
Onboard Graphics	HDMI™	1
	D-Sub	1
Power	Annual Energy Consumption (KWh)	21
	Power Supply Type	External Adaptor 12V 2.5A
	Power Input	100~240V, 50/60Hz
	Adapter's KC safety Number	HU10450-16075
	Power Cord Type	C13
	QC Output Power	N/A
	PD Output Power	N/A

PRO MP241X

PRO MP241X

In The Box	3.5mm Mic Cable	N/A
	Switch Case	N/A
	Portable Screen Protection Case	N/A
	Monitor Hood	N/A
	Speaker (Accessories)	N/A
	DisplayPort Cable	0
	HDMI™ Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	Mouse Bungee Unit	0
	VESA Screw	0
	Power Cord	1
	AC Adaptor	1
	Warranty Card	1
	Quick Guide	1
Design	Adjustment (Tilt)	-5° ~ 15°
	VESA Mounting	75x75mm
	Frameless Design	Yes
Outer Carton Dimension (WxDxH)	Outer Carton Dimension (WxDxH) (mm)	631 x 139 x 433
	Outer Carton Dimension (WxDxH) (inch)	24.84 x 5.47 x 17.05
Product Dimension with Stand (WxDxH)	Product Dimension with Stand (WxDxH) (mm)	541.79 x 180.8 x 416.61
	Product Dimension with Stand (WxDxH) (inch)	21.33 x 7.12 x 16.4
Product Dimension without Stand (WxDxH)	Product Dimension without Stand (WxDxH) (mm)	541.79 x 48.38 x 322.18
	Product Dimension without Stand (WxDxH) (inch)	21.33 x 1.9 x 12.68
Stand Dimension (WxDxH)	Stand Dimension (WxDxH) (mm)	230 x 180.826 x 168.244
	Stand Dimension (WxDxH) (inch)	9.06 x 7.12 x 6.62
Dimension & Weight	Inside Carton Dimensions (WxDxH) (mm)	616 x 125 x 409
	Inside Carton Dimensions (WxDxH) (inch)	24.25 x 4.92 x 16.1
	Weight (Net kg)	2.85
	Weight (Gross kg)	4.27
Weight	Weight Without Stand (kg)	2.5
Warranty	Warranty	24M