

Entrez dans un nouveau monde de possibilités



Picture and logos

SELLING POINTS

- Écran 24,5" pour un affichage plus large
- Le meilleur format pour travailler
- Certification TÜV pour protéger vos yeux
- Technologie MSI EyesErgo avec technologie antiscintillement
- Taux de rafraîchissement de 100 Hz pour des images plus fluides
- Fonction MSI Eye-Q Check pour prendre soin de vos yeux et vous rappeler de faire une pause
- Connectique polyvalente avec ports HDMI™ et DisplayPort
- Système de gestion des câbles amovible pour un environnement bien rangé
- Support de la norme de fixation VESA et fente pour accessoires
- Deux haut-parleurs intégrés



1. 1x entrée alimentation
2. 1 x DP (1.4a)
3. 1 x HDMI™ (2.0b)
4. 1 x sortie audio
5. 1 x encoche Kensington
6. 1 x joystick de navigation à 5 directions

SPECIFICATION

Modèle	Part No	9S6-3PC4CT-017
	Color	ID1/Black-Black
Affichage	Screen Size	24.5" (62.2cm)
	Active Display Area (mm)	543.774(H)x302.616(V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.2832(H)x0.2802(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48 ~ 100Hz
	SDR Brightness (nits)	300
	Contrast Ratio	1300:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	30~113 KHz (H) / 48~100 Hz(V)
	Refresh Rate	100HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	87.32%/79.16%
	NTSC (CIE1931 area percentage/overlap)	72.63%/70.44%
	sRGB (CIE1976 area percentage/overlap)	100.15%/97.18%
	sRGB (CIE1931 area percentage/overlap)	102.55%/96.03%
	Adobe RGB (CIE1976 area percentage/overlap)	85.82%/84.71%
	Adobe RGB (CIE1931 area percentage/overlap)	76%/74.31%
	DCI-P3 (CIE1976 area percentage/overlap)	79.76%/79.71%
	DCI-P3 (CIE1931 area percentage/overlap)	75.59%/75.58%
	Rec.709 (CIE1976 area percentage/overlap)	100.15%/97.18%
	Rec.709 (CIE1931 area percentage/overlap)	102.55%/96.03%
	Rec.2020 (CIE1976 area percentage/overlap)	58.12%/58.12%
	Rec.2020 (CIE1931 area percentage/overlap)	54.23%/54.23%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
	Color bit	10 bits (8 bits + FRC)
Ports E/S	Headphone-out	1
	Lock type	Kensington Lock
	Speaker	2x 2W
	HDMI	1
	HDMI version	2.0b
	HDMI HDCP version	1.4
	DisplayPort	1
	DisplayPort version	1.4a
	DisplayPort HDCP version	1.3
Garantie	Warranty	24M
Alimentation	Power Type	Power Cable
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	18
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E
	Power Cord Type	C13

Accessoires	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	557.7 x 207.2 x 416.3
	Product Dimension without Stand (WxDxH) (mm)	557.7 x 48.1 x 322.9
	Stand Dimension (WxDxH) (mm)	227.8 x 207.2 x 146.28
	Weight (Net kg)	3.3
	Weight Without Stand (kg)	2.8
Dimensions et poids (carton)	Inside Carton Dimension (WxDxH) (cm)	63 x 12.5 x 41
	Outer Carton Dimension (WxDxH) (cm)	64.7 x 13.9 x 43.2
	Weight (Gross kg)	4.9
Code-barre	EAN	4711377333528