

PATH TO THE FUTURE

Découvrez l'écran gaming esport MSI MAG 274F ! Cet écran de 27" à dalle Rapid IPS et résolution Full HD offre un taux de rafraîchissement de 200 Hz et un temps de réponse de 0,5 ms (gris à gris, minimum) qui vous permettent de prendre l'avantage sur vos adversaires dans toutes vos parties !



Picture and logos

SELLING POINTS

- Dalle Rapid IPS pour des couleurs et une luminosité optimales
- Taux de rafraîchissement de 200 Hz pour un affichage sans ralentissement
- Temps de réponse gris à gris de 0,5 ms pour des images sans déchirures ni saccades
- Nouvelle technologie AI Vision cadencée par l'IA pour mieux discerner les détails dans les zones sombres
- Réduction de la lumière bleue grâce à une solution logicielle



1. Bouton de navigation à 5 directions
2. HDMI™ 2.0b (FHD@200Hz)
3. DisplayPort 1.2a (HBR2)
4. Sortie audio
5. Entrée alimentation
6. Encoche Kensington

SPECIFICATION

Modèle	Part No	9S6-3CE41H-045
	Color	ID1/Black-Black
Affichage	Screen Size	27" (68.58 cm)
	Active Display Area (mm)	597.888(H) x 336.312(V)
	Curvature	Flat
	Panel Type	Rapid IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.3114(H)x0.3114(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~200Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	1000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	55.68~218.16 KHz(H) / 48~200 Hz(V)
	Refresh Rate	200HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	0.5ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	88.4%/79.8%
	NTSC (CIE1931 area percentage/overlap)	74.8%/72.3%
	sRGB (CIE1976 area percentage/overlap)	101.4%/98.2%
	sRGB (CIE1931 area percentage/overlap)	105.6%/98.6%
	Adobe RGB (CIE1976 area percentage/overlap)	86.8%/85.6%
	Adobe RGB (CIE1931 area percentage/overlap)	78.3%/75.5%
	DCI-P3 (CIE1976 area percentage/overlap)	80.8%/80.7%
	DCI-P3 (CIE1931 area percentage/overlap)	77.9%/77.9%
	Rec.709 (CIE1976 area percentage/overlap)	101.4%/98.2%
	Rec.709 (CIE1931 area percentage/overlap)	105.6%/98.6%
	Rec.2020 (CIE1976 area percentage/overlap)	58.8%/58.8%
	Rec.2020 (CIE1931 area percentage/overlap)	55.9%/55.9%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
	Color bit	10 bits (8 bits + FRC)
Ports E/S	Headphone-out	1
	Lock type	Kensington Lock
	HDMI	1
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	2.3
Garantie	Warranty	36M
Alimentation	Power Type	External Adaptor 12V 3A
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	26
	Annual Energy Consumption (KWh)	26
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0..3
	Energy Efficiency Rating	F
	Power Cord Type	C13



É C R A N S G A M I N G

MAG 274F

M A G 2 7 4 F

Accessoires	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	1
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	613.5 x 249.7 x 438.5
	Product Dimension without Stand (WxDxH) (mm)	613.5 x 62.1 x 362.5
	Stand Dimension (WxDxH) (mm)	340 x 250 x 143
	Weight (Net kg)	4.2
	Weight Without Stand (kg)	3.7
Dimensions et poids (carton)	Inside Carton Dimension (WxDxH) (cm)	68.3 x 12.7 x 44.8
	Outer Carton Dimension (WxDxH) (cm)	69.8 x 14 x 46.7
	Weight (Gross kg)	6.25
Code-barre	EAN	4711377331647