

PATH TO THE FUTURE

Vivez intensément votre victoire avec l'écran gaming MAG 27C6X ! Avec une résolution de 1920 x 1080, un taux de rafraîchissement de 250 Hz (OC) et un temps de réponse MPRT de 1 ms, l'écran MAG 27C6X sera votre meilleur allié pour prendre l'avantage sur vos adversaires.



Picture and logos

SELLING POINTS

- Dalle VA pour un temps de réponse MPRT de 1 ms et des couleurs et une luminosité optimales
- Taux de rafraîchissement de 250 Hz (OC) pour un affichage sans ralentissement
- Temps de réponse MPRT de 1 ms pour des images sans déchirures ni saccades
- AI Vision pour mieux discerner les détails dans les zones sombres mais également améliorer la luminosité et la saturation des couleurs
- Adaptive-Sync pour des images extrêmement fluides
- Technologie HDR qui améliore les contrastes et les ombres pour des images plus détaillées
- Réduction de la lumière bleue pour une utilisation confortable



1. 5-Way Joystick Navigator
2. AC-in
3. 2 x HDMI™ (2.0b)
4. DisplayPort (1.2a)
5. Headphone out
6. Kensington Lock

SPECIFICATION

Modèle	Part No	9S6-3CE01M-043
	Color	ID1/Black-Black
Affichage	Screen Size	27" (68.58 cm)
	Active Display Area (mm)	597.888(H)x336.312(V)
	Curvature	Curve 1500R
	Panel Type	VA
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.3114(H)x0.3114(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~250Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	250
	Contrast Ratio	3000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	54.24~1125 KHz(H) / 48~250 Hz(V)
	Refresh Rate	250Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	86%/82%
	NTSC (CIE1931 area percentage/overlap)	75%/73%
	sRGB (CIE1976 area percentage/overlap)	99%/90%
	sRGB (CIE1931 area percentage/overlap)	108%/95%
	Adobe RGB (CIE1976 area percentage/overlap)	85%/80%
	Adobe RGB (CIE1931 area percentage/overlap)	78%/75%
	DCI-P3 (CIE1976 area percentage/overlap)	78%/77%
	DCI-P3 (CIE1931 area percentage/overlap)	77%/77%
	Rec.709 (CIE1976 area percentage/overlap)	99%/90%
	Rec.709 (CIE1931 area percentage/overlap)	108%/95%
	Rec.2020 (CIE1976 area percentage/overlap)	55%/55%
	Rec.2020 (CIE1931 area percentage/overlap)	54%/54%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
	Color bit	10 bits (8 bits + FRC)
Ports E/S	Headphone-out	1
	Card reader	N/A
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	2.3
Garantie	Warranty	36M
Alimentation	Power Type	Power Cable
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	21
	Annual Energy Consumption (KWh)	31
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E
	Power Cord Type	C13

Accessoires	DisplayPort Cable	1
	HDMI Cable	0
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	610.5 x 249.8 x 451.6
	Product Dimension without Stand (WxDxH) (mm)	610.5 x 90.4 x 362.5
	Stand Dimension (WxDxH) (mm)	339.8 x 249.7 x 142.7
	Weight (Net kg)	3.95
	Weight Without Stand (kg)	3.56
Dimensions et poids (carton)	Inside Carton Dimension (WxDxH) (cm)	68.4 x 15.8 x 47.5
	Outer Carton Dimension (WxDxH) (cm)	70.4 x 17.8 x 50.8
	Weight (Gross kg)	6.51
Code-barre	EAN	4711377331319